

IN THE SPECIFICATION:

Please replace the third full paragraph on page 7 with:

The outlet port 167 of the valve 165 is adapted to mate with a first end ~~182~~ 180 of a tubing adapter 180. The tubing adapter 180 includes a second end 181 having a barb fitting for coupling with flexible tubing. The second end 181 of the adapter 180 connects to a first end 183 of a diluent supply tube 146. The diluent supply tube 146 further includes a second end 184 that is adaptable to a first inlet port 185 of the mixing union 145. The mixing union 145 further includes an outlet port 187.

Please replace the last indented paragraph on page 8 with:

As shown in Figure 2a, a product dispenser 200 includes a drip tray 101 with a drain 105, and a cup rest 125. The drip tray 101 is typically removable for cleaning. The cup rest 125 fits into the drip tray ~~101~~ 100, thereby providing a level surface for cups to rest on while being filled. The drain 105, when connected to a suitable sewage disposal system, allows for easy disposal of drip tray food contents and cleansing fluids.

Please replace the last indented paragraph on page 9 with:

The drip tray sanitizing system 100 may further include a pump switch 141 and a valve switch 166 as shown in Figure 3a for activation by an operator. Power is supplied from the power supply 161 to the pump 140 and the valve 165 when the switches 141 and 166 are depressed. The switches 141 and 166 may be activated manually by an operator to provide power to the pump 140 and the valve ~~165~~ 166.